

FEROCOAT 297

ANTI-WELD SPATTER COATING



DISCRIPTION

FEROCOAT 297 combines a variety of lubricating soaps and synthetics which provide the maximum in cleaning and lubrication. FEROCOAT 297 can also be used where parts are welded to prevent weld splatter from sticking to the work. FEROCOAT 297 will not interfere with welding, and allows splatter to be easily brushed off work piece.

FEROCOAT 297 contains no phosphates and is completely biodegradable.

CHEMICAL AND PHYSICAL DATA:

Appearance	Visual	Clear, colorless liquid
Density, 20°C	DIN 51757	1.013
pH	DIN 51369	7.0

APPLICATION AND DOSAGE

Generally, FEROCOAT 297 is applied with a 1:1 to 2:1 pump. If required, FEROCOAT 297 can be applied with a roller or brush.

Packing: Steel drum: 210 kg/Drum

Only valid in combination with EC Safety Data Sheet

The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied since the use of our products is beyond our control. Statements concerning the use of PETROFER products are not to be construed as recommending the infringement of any patent.

PETROFER CHEMIE, Römerring 12-16, D-31137 Hildesheim; Phone + 49 51 21 / 76 27-0, Fax + 49 51 21 / 5 44 38
 Mail: info@petrofer.com, Web: <http://www.petrofer.com>

Imported and Distributed by Hong Dang Saigon Chemical Co., Ltd

Telephone: +84 28 6678 1188